



## Product Data: ALKYD ZONE MARKING PAINT

*"As Durable as the Hills of Old New England."*

**DESCRIPTION:** A conventional dry (non-heated) solvent based alkyd zone marking paint, primarily used for parking lots with low to medium traffic. Conforms to TT-P-85E as well as TT-P-115E Type I & M-248 Type S specifications. Not recommended for use over seal coating or on concrete containing silicone.

**SURFACE PREPARATION:** All surfaces should be clean and dry, free of dirt, sand, grease, oil, salt, etc. Loose and lifting paint should be removed prior to painting. While new asphalt surfaces vary in length of time required for curing, insufficient curing may result in bleeding. New concrete tends to chalk, alkyd may also react with the alkali in new concrete making adhesion difficult. Regardless of surface condition a test stripe should be placed inconspicuously to determine if surface is suitable before continuing.

**APPLICATION:** May be applied with conventional or airless sprayers. See equipment manufacturer's recommendations. Recommended paint thickness is 15 mils wet. For best results apply when air and surface temperature are above 40° F and relative humidity is below 85%.

**THINNING & CLEANING:** Thinning is not normally required. If necessary use Toluene, not to exceed 1 quart/5 gallons of paint. Adding solvent may prolong dry time and lead to bleeding of asphalt. Toluene may also be used for cleaning.

**SHELF LIFE:** 12 months minimum based on unopened container stored @ 77° F

**STORAGE:** Store in a cool dry area. **KEEP FROM FREEZING**

**Never Mix waterborne and alkyd traffic paints! The results will be a congealed mess.**

	<b>2000 WHITE</b>	<b>2001 YELLOW (Lead Free)</b>
Coverage/gal (15mils wet 4"line)	320'	320'
Dry time minutes 15 mils wet (LAB)	10	10
Hiding (contrast ratio)	.96	.96
Viscosity (K.U.)	78-85	78-85
Weight/gallon	12.1	12.2
Directional reflectance	84	55
VOC's (pounds/gallon)	2.8	2.8
%Total solids (weight)	77	77
% Non-volatile Vehicle	41	41
Vehicle type	<b>Medium oil solvent based alkyd</b>	

**Franklin Paint Company, Inc.**  
**259 Cottage Street**  
**Franklin, MA 02038**

**Tel: 800-486-0304**  
**508-528-0303**  
**Fax: 508-528-8152**

[www.franklinpaint.com](http://www.franklinpaint.com)