

Franklin Paint Company

259 Cottage Street Franklin, MA 02038
800-486-0304 Fax: 508-528-8152

SAFETY DATA SHEET

SDS Review Date: 06/14/15

SDS Version Number: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND COMPANY

1.1. Product identifier

Product Form: *Blue Liquid*
Product Name: *Winning Streak*
Product Code: *2203*

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use for field marking.

1.3. Details of the supplier of the safety data sheet

Franklin Paint Company, Inc.
259 Cottage St.
Franklin, MA 02038
www.franklinpaint.com

1.4. Emergency telephone number

Emergency Information number: CHEMTEL 800-255-3924
Product Information number: OFFICE 800-486-0304

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS-US classification

Classification	Hazard Category	Hazard Number
<i>Serious eye damage/eye irritation</i>	<i>2B</i>	<i>H320</i>
<i>Specific target organ toxicity – single exposure</i>	<i>3</i>	<i>H335</i>
<i>Carcinogenicity</i>	<i>1A</i>	<i>H350</i>

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) – **DANGER**

Hazard statements (GHS-US)

*Causes eye irritation (H320)**May cause respiratory irritation (H335)**May cause cancer (H350)*

Precautionary statements (GHS-US)

*Obtain special instructions before use. (P201)**Do not handle until all safety precautions have been read and understood. (P202)**Wash thoroughly after handling. (P264)**Wear protective gloves/protective clothing/eye protection/face protection. (P280)**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. (P305 + P351 + P338)**If eye irritation persists get medical advice/attention. (P337 + P313)**Avoid breathing dust/fumes/gas/mist/vapors/spray. (P261)**Use only outdoors or in a well ventilated area. (P271)**IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304 + P340)**Call a POISON CENTER/doctor if you feel unwell. (P312)**Store in a well ventilated place. Keep container tightly closed. (P403 + P233)**Store locked up. (P405)**Dispose of contents/container in accordance with local/regional/national/international regulation. (P501)***2.3. Other hazards***None known***2.4. Unknown acute toxicity (GHS-US)***No data available***SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1. Substances***Not applicable***3.2. Mixture**

Component	CAS No. EC No.	Percent	Hazard class / category / statement
Calcium Carbonate	471-34-1 207-439-9	10.0 – 42.0	
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	25265-77-4 246-771-9	0.5 – 2.0	

Aqua Ammonia	7664-41-7 231-635-3	< 1	Eye Irrit. 2B; H320 STOT SE 3; H335
Crystalline Silica	14808-60-7 EC No. NA	0.1 – 0.99	Carc. 1A; H350

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General	<i>No hazards which require special first aid measures.</i>
Inhalation	<i>If overexposed to mist or dust above published exposure limits, move to fresh air. If symptoms persist, call a physician.</i>
Skin Contact	<i>Wash off immediately with soap and plenty of water removing all contaminated clothing necessary.</i>
Eye Contact	<i>Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.</i>
Ingestion	<i>Rinse mouth with water and afterwards drink plenty of water. Do not induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.</i>

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Water, dry chemical, or carbon dioxide.

Unsuitable extinguishing media: None

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide, and organic products of decomposition may be released in case of fire. Closed container may rupture if strongly heated.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Assure sufficient ventilation.

Use personal protective clothing.

Use NIOSH approved respiratory protection if exposed to vapors, dust, mist, or aerosols above published exposure limits.

6.2. Environmental precautions

Product sinks in water. Prevent spilled material from entering waterways or soil. Product contains no chemical ingredients with an established CERCLA Reportable Quantity (RQ) for spills and releases.

6.3. Methods and material for containment and cleaning up

Absorb spill with inert material and place in a chemical waste container. Dispose of in accordance with federal, state, provincial and local laws and regulations. Remove large quantities mechanically by pumping.

6.4. Reference to other sections

See Section 8 for exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Avoid contact with skin, eyes and clothing.

Avoid breathing vapors, spray mists or sanding dust.

Wear impermeable rubber gloves.

Wash thoroughly after handling.

In case of insufficient ventilation, wear suitable respiratory equipment.

Remove contaminated clothing and wash it before reuse.

Do not eat, drink, smoke or chew tobacco around material.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: *Store container at temperatures above 5 °C (40 °F) and less than 49 °C (120 °F). Keep out of the reach of children.*

Incompatible products: *Strong acids, strong bases, strong oxidizers.*

Incompatible materials: *Lithium metal, sodium metal.*

7.3. Specific end use(s)

No additional information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Chemical Name	ACGIH & Canada	OSHA & Mexico
Calcium Carbonate	10 mg/m ³ - TWA total 3 mg/m ³ – TWA respirable	15 mg/m ³ - TWA total 5 mg/m ³ - TWA respirable
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not established	Not established
Crystalline Silica	0.025 mg/m ³ 8hr TWA	10 mg/m ³ / (%SiO ₂ +2) TWA respirable

8.2. Exposure controls

Provide general and/or local exhaust ventilation to maintain airborne levels below the exposure limits in Section 8. Refer to the current edition of 'Industrial Ventilation: A Manual of Recommended Practice' published by the American Conference of Government Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

8.3. Personal protective equipment

- Protective Measures** *Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.*
- Hygiene Measures** *Take off all contaminated clothing immediately. Follow the usual good standards of occupational hygiene. Clean skin thoroughly after work; apply skin cream.*
- Respiratory Protection** *In case of insufficient ventilation wear NIOSH approved respiratory equipment. If vapor exceeds TLV or PEL, use NIOSH approved air-purifying respirators equipped with organic vapor cartridges. Air-purifying respirators should be equipped with an ammonia methylamine cartridge and dust/mist filter.*
- Hand Protection** *Wear waterproof protective gloves and impervious clothing.*
- Eye Protection** *Use safety glasses with side shields, (ANSI Z87.1 or approved equivalent).*

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

- Appearance** *Blue Liquid*
- Odor** *Ammonia like*

Odor Threshold	5 ppm re ATSDR
pH	6.0 - 8.5
Melting/Freezing Point	32 (°F), 0 (°C)
Boiling Point	212 (°F), 100 (°C)
Flash Point	Not Applicable
Evaporation rate	1 (water = 1)
Flammability (solid, gas)	Not applicable
Lower Explosion Limit	Not applicable
Upper Explosion Limit	Not applicable
Vapor Pressure	40 mmHg
Vapor Density	Not available
Density Relative	1.44
Density (lbs/gal)	12.01
Solubility	Water miscible
Wt. % Solids	59.03
Vol. % Solids	40.97
Wt. % Volatiles	40.97
Vol. % Volatiles	59.03
Grams VOCs / liter	34.93
Wt % HAPs	0
Partition coefficient (o/w)	No data
Ignition Temp.	No data
Autoignition Temp.	Not applicable
Decomposition Temp.	No data
Oxidizing Properties	Not applicable
Explosive Properties	Not applicable

9.2. Other information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous polymerization will not occur.

10.2. Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions: Not applicable

10.4. **Conditions to avoid:** *Prevent from freezing.*

10.5. **Incompatible materials:** *Strong acids, strong bases, strong oxidizers.*

10.6. **Hazardous decomposition products:** *Carbon monoxide, carbon dioxide, and organic products of decomposition may be released in case of fire.*

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicokinetics, Metabolism and Distribution No data

Caustic Burning/Irritation Of Skin

Calcium Carbonate *Irritating*

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate *Rabbit, 24 hr, slight*

Serious Eye Damage/Eye Irritation

Calcium Carbonate *Irritating*

Acute Oral Toxicity

Calcium Carbonate *LD50 Rat 6450 mg/kg*

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate *LD50 Rat 3200 mg/kg*

Acute Inhalational Toxicity

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate *LC50 Rat inhalation > 3500 mg/m 36 hr*

Acute Dermal Toxicity

2,2,4-trimethyl-1,3-pentanediol monoisobutyrate *LD50 skin Guinea pig > 19000 mg/kg*

Respiratory/Skin Sensitization *No information available*

Mutagenicity Assessment *No information available*

Carcinogenicity

Crystalline Silica *IARC 1, NTP - Known to be a human carcinogen.*

Reprotoxicity/Teratogenicity *No information available*

CMR Assessment *No data*

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

2,2,4-trimethyl-1,3-pentanediol > 77 % (28 d, Ready Biodegradability: CO2 Evolution Test)
monoisobutyrate Readily biodegradable

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

No information available

12.5. Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste in accordance with local, state, and national regulations.

SECTION 14: TRANSPORTATION INFORMATION

US DOT Hazard Classification: *Not regulated*

Canadian TDG Classification: *Not regulated*

Air transport ICAO/IATA: *Not regulated*

Shipment by sea IMDG/GGVSee: *Not regulated*

SECTION 15: REGULATORY INFORMATION

15.1. US regulations

CERCLA (EPA) *See Section 6 above.*

SARA TITLE III (EPA) *Product contains the following chemicals listed as Toxic Chemicals subject to the reporting requirements of SARA Title III §313 and 40 CFR Part 372.*

None

SARA Title III §§311/312 and 40 CFR 370 Tier II & MSDS reporting is required for the uncured product as a whole above the 10,000 lb “on-site at any time” threshold as:

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Not subject to SARA Title III §302(c) and 40 CFR 355 Threshold Planning Quantity (TPQ) requirements.

TSCA (EPA) Product complies with US TSCA inventory requirements.

Clean Air Act (EPA): Product contains the following chemicals listed as a Hazardous Air Pollutant (HAP) under Section 112 :

None

Product contains the following chemicals listed as Risk Management (RMP) chemicals under Section 112r:

None

15.2. International regulations

Canada

Canadian DSL (Domestic Substances List) Inventory – All chemical ingredients of this product are listed or exempted.

EU-Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Amending & repealing EC No 1272/2008 Directives 67/548/EEC & 1999/45/EC, and amending (EC) No 1907/2006:

None

15.3. US State regulations

CALIFORNIA PROP 65 Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Crystalline Silica (as respirable dust)

State Right to Know Lists	CA	FL	NJ	PA	MN	MA	RI
Calcium Carbonate	No	Yes	Yes	Yes	Yes	Yes	Yes
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	No	No	No	No	No	No	No
Crystalline Silica	Yes	Yes	Yes	Yes	Yes	Yes	Yes

SECTION 16: OTHER INFORMATION

	Health	Flammability	Physical Hazard
HMIS rating	2*	0	0
NFPA rating	2	0	0

HMIS Hazard Ratings

4 = severe

3 = serious

2 = moderate

1 = slight

0 = minimal

N = no rating for powders

* = chronic health hazard

NFPA Hazard Ratings

4 = extreme

3 = high

2 = moderate

1 = slight

0 = insignificant

N = no rating for powders

Acronyms Legend

- ACGIH** American Conference of Governmental Industrial Hygienists
- ATSDR** Agency for Toxic Substances and Disease Registry
- c.c.** closed cup
- Carc** Carcinogen
- CAS** Chemical Abstract Services
- CERCLA** Comprehensive Environmental Response – Compensation and Liability Act
- CFR** Code of Federal Regulations
- CMR** Carcinogenic-Mutagenic-Toxic for Reproduction
- DOT** Department of Transportation
- EC50** half maximal effective concentration
- EPA** Environmental Protection Agency
- ERG** Emergency Response Guide Book
- Flam. Liq.** Flammable Liquid
- GHS** Globally Harmonized System of Classification and Labeling of Chemicals (GHS)
- HAP** Hazardous Air Pollutant
- HCS** Hazard Communication Standard
- HMIS** Hazardous Materials Identification System

IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO-TI	International Civil Aviation Organization- Technical Instructions
ID	Identification number
IMDG	International Maritime Dangerous Goods
LC50	50 % Lethal Concentration
LD50	50 % Lethal Dose
mmHg	millimeters of Mercury
MARPOL	International Convention for the Prevention of Pollution from Ships
NFPA	National Fire Protection Association
o. c.	open cup
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration
PBT	Persistent, Bioaccumulative, Toxic
RQ	Reportable Quantity
SARA	Superfund Amendments Reauthorization Act
SDS	Safety Data Sheet
STOT	Specific Target Organ Toxicity
TPQ	Threshold Planning Quantity
UN	United Nations
VOC	Volatile Organic Compounds
WHMIS	Workplace Hazardous Materials Information System

SDS Status: *The information contained herein relates only to the specific material identified. Franklin Paint Company believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Franklin Paint Company urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.*