

Franklin Paint™

259 COTTAGE ST FRANKLIN, MA 02038
www.franklinpaint.com

Product Data: SYNTHETIC FIELD MARKING PAINT

DESCRIPTION: Temporary to permanent Synthetic Turf Paint, specifically formulated for use on synthetic athletic playing fields for sports such as football, soccer, field hockey, lacrosse, etc. supplied ready to use, no dilution required.

APPLICATION: Air and surface temperature should be above 50°F with a maximum relative humidity of 85%. Spraying is the preferred method of application to achieve clean sharp lines. Most conventional line marking machines will perform well. As with any paint to be sprayed straining is highly recommended (latex skins do not re-dissolve when mixed).

THINNING & CLEANING: If thinning of paint is desired, never exceed 1 quart of water per 5 gallons of paint, regardless of whether or not paint is thinned, stir to a smooth uniform consistency. For clean up water is usually sufficient on a daily basis. For a thorough cleaning, soap and warm water is recommended.

SHELF LIFE: 12 months minimum based on unopened container stored @ 77°F

STORAGE: Store in a cool dry area. **KEEP FROM FREEZING**

	2250 WHITE	COLORS (ALL)
Coverage/Gal (5 mils wet 4" line)	960'	960'
State	Liquid	Liquid
Hiding	Very High	Very High
Viscosity-KU (Kreb Units)	70-74	70-74
Weight/Gallon (lbs.)	9.6	9.6
Brightness	Very High	High
Whiteness	Very High	N/A
% Total Pigment (By Weight)	15.5	2-5
% Total Solids (By Weight)	24.4	12-14
% Total Vehicle (By Weight)	84.5	95-98
% Titanium Dioxide*	100	N/A

*Primary pigment for brightness, whiteness & hiding