Hydrophast®

FAA Fast Dry Waterborne Traffic Paint

PRODUCT CODES: 2014 (WHITE) | 2015 (YELLOW) | 2015SP (YELLOW)
7002 (GREEN) | 2023 (BLACK) | 7004 (BLUE) | 7005 (RED)

PRODUCT DATA SHEET

Product Description

Hydrophast® is a lead-free, fast drying, 100% acrylic waterborne traffic paint that adheres to stringent environmental safety standards. It provides cost-effective solutions for traffic management through a smooth and uniform application and conforms with Federal Specification TT-P-1952E Type I & II, Federal Specification TT-P-1952F Type I & II, & and FAA Advisory Circular 150/5370-10H.

Product Advantages

- Low VOC- below 100 g/L
- Fast dry for easy traffic control
- Easy clean up with water
- For use on both concrete & asphalt
- Works well over various sealcoat applications
- Excellent bead retention (can be used without)
- Great for airfields, symbols, legends, & lane markings
- Methanol free
- Conforms to FAA Advisory Circular 150/5370-10H
- Conforms to Federal Specification TT-P-1952F Type I & II

Product Properties

Property	Value
Coverage/Gal (15 mils wet, 4" line)	320'
Dry Time (ASTM D-711)	<10 minutes
No Track Time (15 mils wet, 77°F, 45-55% Relative Humidity, 6-8 lbs. glass beads/gallon)	<90 seconds
Dry Opacity (Contrast Ratio)	>0.93 (white/colors) ≥1.00 (black)
Viscosity (Krebs units)	80-90
Density (lbs./gal)	13.8-14.2
Directional Reflectance (Cap Y)	>88 (white) >50 (yellow)
VOC g/L	<100
% Total Solids by Weight	76.0 minimum
% Total Pigment by Weight	60.0-62.0
% Vehicle Solids by Weight	42.0 minimum

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM

Hydrophast®

FAA Fast Dry Waterborne Traffic Paint

PRODUCT CODES: 2014 (WHITE) | 2015 (YELLOW) | 2015SP (YELLOW)
7002 (GREEN) | 2023 (BLACK) | 7004 (BLUE) | 7005 (RED)

PRODUCT DATA SHEET

Surface Conditions

Surfaces must be cured, clean, dry, and free from oil, grease, antifreeze, sand, and other debris and/or chemicals. Remove all loose or lifting paint prior to application. Existing coatings may interfere with adhesion.

New concrete & asphalt should be completely cured before applying (30 days for concrete, 14 days for asphalt is recommended). Check with Franklin Paint technical for more information. If surface condition cannot be determined, a test stripe should be applied in an inconspicuous location.

Application

Formulated for airless or conventional air-atomized spray equipment. For best results, apply when air and surface temperatures are above 50°F and relative humidity is below 85%.

Cold paint may be heated to 110°F for desired flow properties. Heating waterborne paint *will not* accelerate dry time.

Storage & Shelf Life

⚠ **KEEP FROM FREEZING!**

Store in a cool, dry area indoors, out of direct sunlight, ideally at 60–70°F.
Minimum 12 months shelf life when stored unopened, at these conditions.

Cleaning

Wet paint may be cleaned with water. Dried paint is very difficult to remove.

Limitations

- Never mix waterborne paint with any other paint products.
- Not recommended for use over silicone sealers.
- Do not apply when rain is in forecast.
- Do not apply when temperatures expected to fall below 32°F within 6 hours of application.
- Low temperatures and high humidity can slow dry time.
- Keep from freezing at all times.

The technical information and suggestions for use and applications presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions. Potters Industries LLC makes no warranties, either expressed or implied, with respect to our materials, including the warranties of merchantability or fitness for any particular purpose. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses.

©2026 Potters Industries LLC. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior permission of the publisher and copyright holder.

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM