Half Time®

Athletic Field Marking Paint

PRODUCT CODES: 2205 (WHITE)

VARIOUS - YELLOW | RED | BLUE | BLACK | ORANGE | PINK

PRODUCT DATA SHEET

Product Description

Formulated for use on grass athletic fields for sports including but not limited to football, soccer, field hockey, and lacrosse. Can be used on synthetic turf where durability is not required. Supplied ready for use, no dilution required.

Product Advantages

- Prediluted, ready for use, stir & spray formulation
- Environmentally safe
- Easy clean up with water
- For use on natural and various synthetic turfs
- Available in custom colors

Product Properties

Property	Value
Coverage/Gal (5 mils wet, 4" line)	960'
Consistency	Liquid
Viscosity (Krebs units)	70-74
Density (lbs./gal)	11.2-11.4
% Total Solids by Weight	49.0-50.0
% Total Solids by Volume	31.0 minimum
% Total Pigment by Weight	40.0-42.0
% Total Vehicle by Weight	58.0-60.0
% Rutile Titanium Dioxide of Pigment (by weight)	5.5 (white)
% Calcined Clay of Pigment (by weight)	42.1 (white)
% Calcium Carbonate of Pigment (by weight)	52.4 (white)

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM

Half Time®

Athelic Field Marking Paint

PRODUCT CODES: 2205 (WHITE)

VARIOUS - YELLOW | RED | BLUE | BLACK | ORANGE | PINK

PRODUCT DATA SHEET

Surface Conditions

Surface must be clean, dry, and free of dirt, dust, loose debris, standing water, frost, grease, oil, or other contaminants that may interfere with application performance or adhesion.

Application

Formulated for use with conventional spray equipment. No dilution required, stir and spray paint. For best results, apply when air & surface temperatures are above freezing, and surface is dry.

Storage & Shelf Life

⚠ KEEP FROM FREEZING!

Store in a cool, dry area indoors, out of direct sunlight, ideally at 60–70°F.
Minimum 12 months shelf life when stored unopened, at these conditions.

Cleaning

Wet paint may be cleaned with water. For a more thorough cleaning, soap and warm water is recommended.

Limitations

- Do not apply when rain is in forecast.
- Low temperatures and high humidity can slow dry time.
- Damp surfaces will slow dry time.
- Keep from freezing at all times.

The technical information and suggestions for use and applications presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions. Potters Industries LLC makes no warranties, either expressed or implied, with respect to our materials, including the warranties of merchantability or fitness for any particular purpose. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses.

©2026 Potters Industries LLC. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior permission of the publisher and copyright holder.

Potters Innovating Responsibly Since 1914

Franklin Paint™ 259 COTTAGE ST FRANKLIN, MA 02038 www.franklinpaint.com

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM