Turbo Dry®

Fast Dry Acetone Traffic Paint

PRODUCT CODES: 2090 (WHITE) | 2091 (YELLOW)
2092 (GREEN) | 2093 (BLACK) | 2094 (BLUE) | 2095 (RED)

PRODUCT DATA SHEET

Product Description

Turbo Dry® is a lead-free, durable, extremely fast drying acrylic/alkyd solventborne traffic paint. No pickup in as fast as 30 seconds. Conforms to current federal VOC regulations, as well as stricter VOC limits of 100 g/L in many states. This product is recommended for use on bituminous and concrete pavements.

Product Advantages

- Low VOC- below 100 g/L
- Extremely fast dry for easy traffic control
- Cold weather approved
- For use on both concrete & asphalt
- Bright, no fade color for crisp lines
- Excellent bead retention (can be used without)
- Great for symbols, legends, curbing, concrete poles, & lane marking
- Available in custom colors

Product Properties

Property	Value
Coverage/Gal (15 mils wet, 4" line)	320'
Dry Time (ASTM D-711)	<3 minutes
No Track Time (15 mils wet, 77°F, 45-55% Relative Humidity, 6-8 lbs. glass beads/gallon)	<30 seconds
Dry Opacity (Contrast Ratio)	>0.94 (white/colors) >1.00 (black)
Viscosity (Krebs units)	85-90
Density (lbs./gal)	12.2-12.8
Directional Reflectance (Cap Y)	>85 (white) >50 (yellow)
VOC g/L	<100
% Total Solids by Weight	76.0 minimum
% Total Pigment by Weight	58.0-62.0
% Vehicle Solids by Weight	40.0 minimum

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM

Turbo Dry®

Fast Dry Acetone Traffic Paint

PRODUCT CODES: 2090 (WHITE) | 2091 (YELLOW)
2092 (GREEN) | 2093 (BLACK) | 2094 (BLUE) | 2095 (RED)

PRODUCT DATA SHEET

Surface Conditions

Surfaces must be cured, clean, dry, and free from oil, grease, antifreeze, sand, and other debris and/or chemicals. Remove all loose or lifting paint prior to application. Existing coatings may interfere with adhesion.

New concrete & asphalt should be completely cured before applying (30 days for concrete, 14 days for asphalt is recommended). Test in inconspicuous area if surface condition is uncertain.

Application

Formulated for airless or conventional air-atomized spray equipment. For best results, apply when air and surface temperatures are above 40°F and relative humidity is below 85%.

Do not apply if rain is in forecast. Low temperatures and high humidity can slow dry time.

Storage & Shelf Life

Store in a cool, dry area indoors, out of direct sunlight, ideally at 50–70°F.
Minimum 12 months shelf life when stored unopened, at these conditions.

Cleaning

Toluene or acetone may be used for cleaning. Dried paint is very difficult to remove.

Limitations

- Federal and state regulations prohibit dilution of this product. ***DO NOT THIN.***
- Never mix acetone paint with any other paint products.
- Do not apply when rain is in forecast.
- Low temperatures and high humidity can slow dry time.
- Product may bleed on fresh sealcoat.
- Flammable. ***DO NOT HEAT.***

The technical information and suggestions for use and applications presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions. Potters Industries LLC makes no warranties, either expressed or implied, with respect to our materials, including the warranties of merchantability or fitness for any particular purpose. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses.

©2026 Potters Industries LLC. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior permission of the publisher and copyright holder.

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM