

Winning Streak®

Athletic Field Marking Paint

Product Data

Version 1.0

Product Type: **Concentrated Liquid Paste**

Product Codes: **2200 2210 2240 Various**

Product Colors: **White White White Yellow, Red, Blue,
Premium Ultra Black, Orange, Pink**

Product Description:

Formulated for use on grass athletic fields for sports including but not limited to football, soccer, field hockey, and lacrosse. Can be used on synthetic turf where durability is not required. Supplied in a liquid paste ready for dilution with water.

Product Advantages:

- Concentrated formula to be diluted as needed with water
- Environmentally safe
- Easy clean up with water
- For use on natural and various synthetic turfs
- Available in custom colors
- White Ultra comes formulated with optical brightener, making it a great choice for televised events

Product	2200 White	2210 White Premium	2240 White Ultra
Hiding	High	Very High	Highest
Whiteness	High	Very High	Highest
Brightness	High	Very High	Highest
% Rutile Titanium Dioxide of Pigment (by weight)	9.2	19.4	25.0
% Calcined Clay of Pigment (by weight)	46.0	47.0	75.0
% Calcium Carbonate of Pigment (by weight)	44.8	33.6	0

Application:

Mix 1:1, equal parts water & paint, or any desired ratio never exceeding 3 parts water to 1 part paint. Stir mixture until a smooth uniform consistency is achieved. Formulated for use with conventional spray equipment. For best results, apply when air & surface temperatures are above freezing, and surface is dry.

Physical Properties:

Coverage/Gal (5 mils wet, 4" line)	960'
Coverage/Gal 1:1 (5 mils wet, 4" line)	1920'
Consistency	Liquid Paste
Viscosity (Krebs units)	110-120 115-120 (White Ultra)
Density (lbs./gal)	11.0-11.8
% Total Solids by Weight	48-49 (white) 50-56 (colors)
% Total Solids by Volume	31.0 minimum
% Total Pigment by Weight	36-39 (white) 39-44 (colors)
% Total Vehicle by Weight	60-64 (white) 55-60 (colors)

Cleaning:

Wet paint may be cleaned with water. For a more thorough cleaning, soap and warm water is recommended.

Storage & Shelf Life:

Store in a cool dry area, indoors, and out of direct sunlight, ideally at 60-70°F. Minimum 12 months shelf life when stored unopened, at these conditions. **KEEP FROM FREEZING!**

Limitations:

- Must be diluted and mixed before using.
- Do not apply when rain is in forecast.
- Low temperatures & high humidity can slow dry.
- Damp surfaces will slow dry time.

Franklin Paint™

259 Cottage St
Franklin, MA 02038

Phone
508-528-0303

Fax
508-528-8152

www.franklinpaint.com