Winning Streak®

Athletic Field Marking Paint

PRODUCT CODES: 2200 (WHITE) | 2210 (PREMIUM WHITE) | 2240 (ULTRA WHITE)
VARIOUS - YELLOW | RED | BLUE | BLACK | ORANGE | PINK

PRODUCT DATA SHEET

Product Description

Winning Streak® is specifically formulated for use on grass athletic fields, making it suitable for a range of sports field layouts, including but not limited to football, soccer, field hockey, and lacrosse.

It can also be applied to synthetic turf where durability is not a concern. The product comes in a liquid paste form, ready to be diluted with water.

Product Advantages

- Concentrated formula to be diluted as needed with water
- Environmentally safe
- Easy clean up with water
- For use on natural and various synthetic turfs
- Available in custom colors
- White Ultra comes formulated with optical brightener, making it a great choice for televised events

Product Properties

Property	Value
Coverage/Gal (5 mils wet, 4" line) Coverage/Gal 1:1 (5 mils wet, 4" line)	960' 1920'
Consistency	Liquid Paste
Viscosity (Krebs units)	110-120 115-120 (White Ultra)
Density (lbs./gal)	11.0-11.8
% Total Solids by Weight	48-49 (white) 50-56 (colors)
% Total Solids by Volume	31.0 minimum
% Total Pigment by Weight	36-39 (white) 39-44 (colors)
% Total Vehicle by Weight	60-64 (white) 55-60 (colors)

Product / Property	2200 (White)	2210 (White Premium)	2240 (White Ultra)
Hiding	High	Very High	Highest
Whiteness	High	Very High	Highest
Brightness	High	Very High	Highest
% Rutile Titanium Dioxide of Pigment (by weight)	9.2	19.4	25
% Calcined Clay of Pigment (by weight)	46	47	75
% Calcium Carbonate of Pigment (by weight)	44.8	33.6	0

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM

Winning Streak®

Athelic Field Marking Paint

PRODUCT CODES: 2200 (WHITE) | 2210 (PREMIUM WHITE) | 2240 (ULTRA WHITE)
VARIOUS - YELLOW | RED | BLUE | BLACK | ORANGE | PINK

PRODUCT DATA SHEET

Surface Conditions

Surface must be clean, dry, and free of dirt, dust, loose debris, frost, grease, oil, or other contaminants that may interfere with application performance or adhesion.

Application

Mix 1:1, equal parts water & paint, or any desired ratio never exceeding 3 parts water to 1 part paint. Stir mixture until a smooth uniform consistency is achieved. Formulated for use with conventional spray equipment.
For best results, apply when air & surface temperatures are above freezing, and surface is dry.

Storage & Shelf Life ⚠ KEEP FROM FREEZING!

Store in a cool, dry area indoors, out of direct sunlight, ideally at 60–70°F.
Minimum 12 months shelf life when stored unopened, at these conditions.

Cleaning

Wet paint may be cleaned with water. For a more thorough cleaning, soap and warm water is recommended.

Limitations

- Must be diluted and mixed before using.
- Do not apply when rain is in forecast.
- Low temperatures and high humidity can slow dry time.
- Damp surfaces will slow dry time.
- Keep from freezing at all times.

The technical information and suggestions for use and applications presented herein represent the best information available to us and are believed to be reliable. They should not, however, be construed as controlling suggestions. Potters Industries LLC makes no warranties, either expressed or implied, with respect to our materials, including the warranties of merchantability or fitness for any particular purpose. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses.

©2026 Potters Industries LLC. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying, recording or otherwise, without the prior permission of the publisher and copyright holder.

259 COTTAGE ST,
FRANKLIN, MA 02038
PHONE: 508-528-0303
WWW.FRANKLINPAINT.COM